

CURVE : 19" High Perforation Export Server Rack

Characteristics of the CURVE : 19" High Perforation Export Server Rack

- **Design:** CURVE : 19" High Perforation Export Server Rack is designed and produced to be the Modular Knock-down System which is very easy to assemble.
- **Material:** The rack is made Electro-Galvanized Steel Sheet, durable and 100% rustproof material.
- **Frame:** Vertical Mounted Frame is made of 2.0 mm Electro-Galvanized Steel Sheet which is a thick, durable and 100% rustproof material. It can be adjusted depth of the rack as requirement without removing the side panel.
- **Base:** A base of the rack is made of 2.0 mm Electro-Galvanized Steel Sheet and a base for casters is made of 3.0 mm Electro-Galvanized Steel Sheet which are thick, durable and 100% rustproof.
- **Roof:** The roof of the rack can be installed ventilating fan from 1 unit to 6 units. There are two holes on the roof of the rack to put cables through the holes. It is designed to be a high-roof and it is perforated for ventilation.
- **Front Door:** The front curved door is perforated for ventilation (each hole is 4P 4.8 mm in size). The front door has a handle-lock for security. The door can be set to right swing open or left swing open.
- **Rear Door:** The rear door is perforated for ventilation (each hole is 4P 4.8 mm in size). It has a handle-lock for security. The rear door is designed to decrease doorway and is divided into left and right flat pieces.
- **Bottom Rack:** The bottom rack can put cables through the hole. The inside of the bottom rack, it can be adjustable for stands with screws.
- **Side Panel:** The side panel secures with a turn-lock and two latch-locks. It is convenient to maintain.
- **Stands:** The rack has four stands which are easy to adjust inside and outside the rack as requirement.
- **Casters:** The rack has four casters which are made of Black Nylon Six. The casters can turn around 360 degree and load 250 Kg./caster. Support loads up to 1,000 kg.
- **Ground System:** There is the Ground System all parts of the rack with the earth cable kit.
- **Color:** The rack is black or white (Optional) which is coated with powder epoxy by Electro-Static System for strength.
- **Accessories:** The rack is designed to provide customers with M6 bolts, cage nuts and plastic washers.
- **Quality Product Standard:** The racks meet quality product standards which are ANIS/EIA-310D-1992 (Rev.EIA-310-C), IEC 60297-1, IEC 60297-2, BS 5954: Part 2, DIN 41494.
- **Manufacturing standard:** ISO 9001: 2000 Company

CURVE : 19" High Perforation Export Server Rack

u	Height (mm.)	Height effective (mm.)	Order NO. (Width* x Depth : mm.)				
1U = 44.45 mm.	H	h	600x670	600x870	600x970	600x1070	600x1170
15U	840	670	HP-6615	HP-6815	-	-	-
27U	1370	1200	HP-6627	HP-6827	HP-6927	HP-6027	-
36U	1770	1600	HP-6636	HP-6836	HP-6936	HP-6036	-
39U	1905	1735	HP-6639	HP-6839	HP-6939	HP-6039	-
42U	2040	1870	HP-6642	HP-6842	HP-6942	HP-6042	HP-6142
45U	2170	2000	HP-6645	HP-6845	HP-6945	HP-6045	HP-6145

Remark: Width* = Require 800 mm. in width, please contact the distributor.

Illustration

